## ANTI-WASH GEOJUTE®

## Solutions to a Multitude of Erosion Control Problems

## Unlimited Applications and Uses, Including:

- Golf course construction and maintenance
- Embankments and slopes
- Civic beautification
- •Landfills
- Highway construction
- •Landscape improvement
- Sod stabilization
- Lakes and stream banks
- Mining reclamation
- Nurseries
- Military bases
- •Industrial and commercial development
- •Farm and agricultural
- Hydroseeding
- Ski slopes
- •Beach and sand dune stabilization
- Pipeline construction
- Wetland reclamation
- Drainage ditches









Yarn Count, Warp	78 per width, minimum
Yarn Count, Weft	45 per linear yard, minimum
Color	Natural (Brown)
Fabric Width (in)	48
Fabric Weight (lb/yd²)	.92
Length (ft)	225
Area (yd <sup>2)</sup>	100
Weight (lbs)	92
Strands/ft, Warp	19.5
Strands/ft, Weft	14
Mass/Unit Area (oz/yd²)	14.7
Wide Width Tensile, Dry (lb/ft)	300x175
Wide Width Tensile, Wet (lb/ft)	125x65
Elongation at Break (%)	10 x 10
Open Area (%)	60 - 65
Durability (year)	1-2
Water Velocity (ft/sec)	8
Unit Sear Test (lb/ft <sup>2</sup> )	0.45

ANTI-WASH **GEOJUTE** distributed by:



EROSION CONTROL, LINERS, GEOTEXTILES, BMP's & SWPPP's

2119 SE COLUMBIA WAY, BLDG #2, STE #280 VANCOUVER, WA 98661

PHONE (360) 699-1426 FAX (360) 699-1344

INFO@CSIGEO.COM

WWW.CSIGEO.COM