

# ANTI-WASH GEOJUTE®

Solutions to a Multitude of Erosion Control Problems

## Unlimited Applications and Uses, Including:

- Golf course construction and maintenance
- Embankments and slopes
- Civic beautification
- Landfills
- Highway construction
- Landscape improvement
- Sod stabilization
- Lakes and stream banks
- Mining reclamation
- Nurseries
- Military bases
- Industrial and commercial development
- Farm and agricultural
- Hydroseeding
- Ski slopes
- Beach and sand dune stabilization
- Pipeline construction
- Wetland reclamation
- Drainage ditches



Yarn Count, Warp	78 per width, minimum
Yarn Count, Weft	45 per linear yard, minimum
Color	Natural (Brown)
Fabric Width (in)	48
Fabric Weight (lb/yd <sup>2</sup> )	.92
Length (ft)	225
Area (yd <sup>2</sup> )	100
Weight (lbs)	92
Strands/ft, Warp	19.5
Strands/ft, Weft	14
Mass/Unit Area (oz/yd <sup>2</sup> )	14.7
Wide Width Tensile, Dry (lb/ft)	300x175
Wide Width Tensile, Wet (lb/ft)	125x65
Elongation at Break (%)	10 x 10
Open Area (%)	60 - 65
Durability (year)	1- 2
Water Velocity (ft/sec)	8
Unit Tear Test (lb/ft <sup>2</sup> )	0.45

ANTI-WASH **GEOJUTE** distributed by:



EROSION CONTROL, LINERS, GEOTEXTILES, BMP'S & SWPPP'S

2119 SE COLUMBIA WAY, BLDG #2, STE #280  
VANCOUVER, WA 98661

PHONE (360) 699-1426

FAX (360) 699-1344

INFO@CSIGEO.COM

WWW.CSIGEO.COM