

TruPave[®] Engineered Paving Mat

Trupave[®] engineered paving mat is a wet-formed fiberglass/polyester hybrid paving mat comprised of randomly dispersed glass and polyester fibers, bonded together with a resinous binder system manufactured by Owens Corning. TruPave[®] engineered paving mat conforms to ASTM D 7239.

Mechanical Properties	Test Method	Unit	Roll Value ¹	
			MD	CD
Tensile Strength	ASTM D 5035	N/50mm (lb/2 in)	200 (45)	200 (45)
Elongation @ max load	ASTM D 5035	%	< 5	< 5
Melting Point	ASTM D 276	C° (F°)	> 230 (>446)	
Asphalt Retention	ASTM D 6140	l/m ² (gal/yd ²)	0.86 (0.19)	
Mass/Unit Area	ASTM D 5261	g/m ² (oz/yd ²)	125 (3.71)	

¹ All test data shall meet or exceed according to Type I, ASTM D 7239.

All mat manufacturing procedures conform to International Organization for Standardization (ISO) 9002.

TruPave[®] is a registered trademark of Owens Corning.

Disclaimer: TenCate Geosynthetics North America assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate Geosynthetics North America disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.